POWERFUL AND SMALL

conga-MA5



- 5th Gen. Intel® Atom™ processor family
- COM Express Mini Type 10 module
- Intel 9th generation (Gen 9) LP graphics
- Up to 4k resolution (4096x2160@60Hz)
- 4K Codec Decode & Encode for HEVC, H.264, VP8

COM Express®

Formfactor	Formfactor COM Express® Mini | (55 x 84 mm) | Type 10
CPU	Intel® Pentium® N4200 — 2.50 GHz (Burst) | 1.1 GHz Clock — Quad Core — L2 cache 2MB — 6W TDP Intel® Celeron® N3350 — 2.40 GHz (Burst) | 1.1 GHz Clock — Dual Core — L2 cache 1MB — 6W TDP Intel® Atom™ x7-E3950 — 2.00 GHz (Burst) | 1.6 GHz Clock — Quad Core — L2 cache 2MB — 12W TDP Intel® Atom™ x5-E3940 — 1.80 GHz (Burst) | 1.6 GHz Clock — Quad Core — L2 cache 2MB — 9W TDP Intel® Atom™ x5-E3930 — 1.80 GHz (Burst) | 1.3 GHz Clock — Dual Core — L2 cache 1MB — 6.5W TDP
DRAM	Dual channel onboard DDR3L memory support for up to 8 GByte at 1866MT/s
Chipset	Integrated in SoC
Ethernet	Intel® I210 (Industrial) / I211 (Commercial) Gigabit Ethernet Controller
I/O Interfaces	4x PCIe Gen2 | 2x USB 3.0/2.0 | 6x USB 2.0 | 2x SATA3 | SDIO | LPC Bus | SMBus | I2C Bus | 2x UART
Onboard storage	eMMC 5.0 interface up to 128GB
Sound	Intel® High Definition Audio (Intel® HD Audio)
Graphics	Intel® HD Graphics Gen 9 | PAVP 2.0 | H.265/HEVC | VP9 | OpenCL 2.0 | OpenGL 4.3 | OpenGL ES 3.0 | DirectX12 | HDCP1.4
LVDS	18/24-bit Single Channel LVDS Interface, resolutions up to 1200X1024@60Hz | VESA standard or JEIDA data mapping Automatic Panel Detection via EDID/EPI | shared with eDP 1.3 supporting up to 3840x2160@60 Hz (option)
Digital Display Interface	DisplayPort 1.2 up to 4096×2160@60Hz or HDMI 1.4b up to 1920×1200@60Hz
congatec Board Controller	Multistage watchdog | non-volatile user data storage | manufacturing and board Information | board statistics I²C bus (fast mode | 400 kHz | multi master) | power loss control
Embedded BIOS Features	AMI Aptio® UEFI 2.x firmware | 8 MByte serial SPI with congatec Embedded BIOS features OEM Logo | OEM CMOS Defaults | LCD Control Display Auto Detection | Backlight Control | Flash Update
TPM	Infineon's Trusted Platform Module (TPM 2.0/1.2) SLB 9665/9660 option
Power Management	ACPI 5 .0 compliant | Smart Battery Management
Operating Systems	Microsoft® Windows 10 Enterprise | Microsoft® Windows 10 IoT Core | Linux Yocto | Android
Power Consumption	Typ. application 6W...12W
Temperature	Commercial : Operating: 0 to +60°C Storage: -20 to +70°C Industrial: Operating: -40 to +85°C Storage: -40 to +85°C
Humidity	Operating: 10 to 90% r. H. non cond. Storage: 5 to 95% r. H. non cond.
Size	55 x 84 mm (2.17" x 3.31")

conga-MA5 | Block diagram



conga-MA5 | Order Information

Article	PN	Description
conga- MA5/E3950-8G eMMC32	048000	COM Express Mini Type10 module with Intel® Atom™ x7-E3950 quad core processor with 1.6GHz core frequency up to 2.0GHz 2MB L2 cache | 8GB 1866MT/s DDR3L onboard memory and 32GB eMMC onboard flash.
conga-MA5/E3940-4G eMMC16	048001	COM Express Mini Type10 module with Intel® Atom™ x5-E3940 quad core processor with 1.6GHz core frequency up to 1.8GHz 2MB L2 cache | 4GB 1866MT/s DDR3L onboard memory and 16GB eMMC onboard flash.
conga- MA5/E3930-2G eMMC16	048002	COM Express Mini Type10 module with Intel® Atom™ x5-E3930 dual core processor with 1.3GHz core frequency up to 1.8GHz 2MB L2 cache | 2GB 1600MT/s DDR3L onboard memory and 16GB eMMC onboard flash.
conga- MA5/i-E3950-8G eMMC16	048010	COM Express Mini Type10 module with Intel® Atom™ x7-E3950 quad core processor with 1.6GHz core frequency up to 2.0GHz 2MB L2 cache | 8GB 1866MT/s DDR3L onboard memory and 16GB eMMC onboard flash. Industrial grade temperature range from -40°C to 85°C.
conga- MA5/i-E3940-4G eMMC16	048011	COM Express Mini Type10 module with Intel® Atom™ x5-E3940 quad core processor with 1.6GHz core frequency up to 1.8GHz 2MB L2 cache | 4GB 1866MT/s DDR3L onboard memory and 16GB eMMC onboard flash. Industrial grade temperature range from -40°C to 85°C.
conga- MA5/i-E3930-4G eMMC16	048012	COM Express Mini Type10 module with Intel® Atom™ x5-E3930 dual core processor with 1.3GHz core frequency up to 1.8GHz 2MB L2 cache | 4GB 1600MT/s DDR3L onboard memory and 16GB eMMC onboard flash. Industrial grade temperature range from -40°C to 85°C.
conga- MA5/N4200-8G eMMC32	048020	COM Express Mini Type10 module with Intel® Pentium® N4200 quad core processor with 1.1GHz core frequency up to 2.50GHz 2MB L2 cache | 8GB 1866MT/s DDR3L onboard memory and 32GB eMMC onboard flash.
conga- MA5/N3350-4G eMMC16	048022	COM Express Mini Type10 module with Intel® Celeron™ N3350 dual core processor with 1.1GHz core frequency up to 2.3GHz 2MB L2 cache | 4GB 1600MT/s DDR3L onboard memory and 16GB eMMC onboard flash.

Coolings		
conga- MA5/i-CSP-T	048050	Passive cooling solution for COM Express Mini Type10 module conga-MA5 with lidded Intel Atom processor. All standoffs are M2.5mm thread.
conga- MA5/i-CSP-B	048051	Passive cooling solution for COM Express Mini Type10 module conga-MA5 with lidded Intel Atom processor. All standoffs are with 2.7mm bore hole.
conga- MA5/i-HSP-T	048052	Standard heatspreader for COM Express Mini Type10 module conga-MA5 with lidded Intel Atom processor. All standoffs are M2.5mm thread.
conga- MA5/i-HSP-B	048053	Standard heatspreader for COM Express Mini Type10 module conga-MA5 with lidded Intel Atom processor. All standoffs are with 2.7mm bore hole.
conga- MA5/CSP-T	048054	Passive cooling solution for COM Express Mini Type10 module conga-MA5 with open silicon Intel Pentium and Celeron processor. All standoffs are M2.5mm thread.
conga- MA5/CSP-B	048055	Passive cooling solution for COM Express Mini Type10 module conga-MA5 with open silicon Intel Pentium and Celeron processor. All standoffs are with 2.7mm bore hole.
conga- MA5/HSP-T	048056	Standard heatspreader for COM Express Mini Type10 module conga-MA5 with open silicon Intel Pentium and Celeron processor. All standoffs are M2.5mm thread.
conga- MA5/HSP-B	048057	Standard heatspreader for COM Express Mini Type10 module conga-MA5 with open silicon Intel Pentium and Celeron processor. All standoffs are with 2.7mm bore hole.

Accessories		
conga-MEVAL	065400	Evaluation carrier board for Type 10 COM Express modules
conga-LDVI/EPI	011115	LVDS to DVI converter board for digital flat panels with onboard EEPROM
COM-Express-carrier-board-Socket-5	400007	Connector for COM-Express carrier boards | height 5mm | packing unit 4 pieces
COM-Express-carrier-board-Socket-8	400004	Connector for COM-Express carrier boards | height 8mm | packing unit 4 pieces

© 2017 congatec AG. All rights reserved.

All data is for information purposes only. Although all the information contained within this document is carefully checked, no guarantee of correctness is implied or expressed. Product names, logos, brands, and other trademarks featured or referred are the property of their respective trademark holders. These trademark holders are not affiliated with congatec AG. Rev. April 12, 2017 MR